

Rilevatori portatili metano e GPL

Portable methane/LPG detectors



SE 151NM

Cercafughe gas con sensore particolarmente sensibile sia al Metano che al GPL. Tarato in aria emette un impulso sonoro al secondo; non appena il sensore si trova in ambiente inquinato la frequenza degli impulsi aumenta. Viene fornito in elegante valigetta in nylon.

Portable gas leak detector calibrated for methane and LPG. In clean air, give one pulse per second. As soon as the air surrounding the sensor is polluted the rate of the pulses will increase until it becomes continuous indicating a gas leakage.



SE 153NM

Cercafughe gas con sensore semiconduttore sensibilissimo alla rilevazione di metano e GPL. Lo strumento provvede automaticamente alla taratura in aria pulita ad ogni accensione. La rilevazione di gas è segnalata tramite l'illuminazione progressiva del display a led posizionato sul frontale e contemporaneamente tramite avvisatore acustico. Il sensore è protetto da concentrazioni di gas troppo elevate, ed è fornito con batterie ricaricabili Ni-MH e la flessibilità della sonda consente di raggiungere gli angoli più angusti.

Latest-generation leak detector with semi-conductor sensor designed to detect concentrations of LPG and methane.

Before use, it is possible to calibrate the sensor for air by the relevant potentiometer. An increase of concentration of the gas detected is signalled by a progressive lighting of the LED bar display and an acoustic signaller.



SE 155M

Caratteristiche tecniche simili al modello "SE151" ma con sensore incorporato e alimentato da una pila da 9V con autonomia di 8 ore. Una barra LED indica la concentrazione di Metano/Gpl. Viene fornito in elegante borsello in nylon.

Its technical specifications are similar to model "SE 151" but with internal sensor powered by a 9V cell with 8 hours standard life. A led bar shows the methane/LPG concentration. It is supplied in a nylon case.



Sensibilità: 20 ppm

Sensitivity: 20 ppm

Alimentazione: 4 x 1.5V (pile incluse)

Power supply: 4 x 1.5V (battery enclosed)

Autonomia: 8 ore

Operation range: 8hours

Autospegnimento: 10min

Automatic switching off: 10min

Valigetta: 220x160x40mm

Case: 220x160x40mm



Sensibilità: 20 ppm

Sensitivity: 20 ppm

Alimentazione: Batterie ricaricabili Ni-MH

Power supply: Rechargeable batteries Ni-MH

Autonomia: 5ore

Operation range: 5hours

Tempo di ricarica: 14ore

Recharge time: 14hours

Autospegnimento: 10min

Automatic switching off: 10min

Valigetta: 280x120x90mm

Case: 280x120x90mm



Sensibilità: 20 ppm

Sensitivity: 20 ppm

Alimentazione: 9 V (pila inclusa)

Power supply: 9V (battery enclosed)

Autonomia: 8ore

Operation range: 8hours

Autospegnimento: 5min

Automatic switching off: 5min

Custodia: 55 x 235 x 37mm.

Case: 55 x 235 x 37mm